Epson EB-L1000 Series

THE POWER TO INSPIRE





EPSON WORLD LEADER IN PROJECTORS²





A NEW ERA OF WIDE SCREEN PRESENTING





Take image quality to new levels with our latest large venue installation range, featuring gamechanging laser projection technology and the world's first 12,000lm WUXGA LCD laser projector³. **Capture audience attention with Full HD resolution** and special 4K enhancement technology that allows users to experience the latest 4K effect.

Visual perfection

Create powerful images in auditoriums, lecture theatres, galleries, shopping centres and more. Our acclaimed 3LCD and laser light source technologies get your message across even in brightly lit rooms with images that have three times brighter colours than the competition¹.

A new world of presenting

Make a big impression with innovative features and presenting tools ranging from flexible 360° installation, motorised changeable lenses and split screen presenting to a time-saving lens memory function and a built-in camera for consistent image calibration.

Outstanding reliability

Enjoy total peace of mind with large screen projectors you can count on. Installation and set-up are very straightforward, while a laser life of up to 56,000 hours and a filter maintenance cycle up to 30,000 hours keeps maintenance to a minimum.





LASER LIGHT

OPTIONAL LENSES



LENS-SHIFT









DIGITAL SPLIT SCREEN

360° INSTALLATION





UST LENS

UP TO 12,000 LUMENS

WUXGA WUXGA



DMX-ARTNET



HD-SDI



POINT CORRECTION



24/7 OPERATION



5 YEAR WARRANTY

LASER LIGHT PRECISION

Experience astonishing quality and reliability with our new laser light source and advanced filter. Combine versatile presenting features with 20,000 hours of maintenance-free use and consistent performance for total peace of mind during important presentations.

Innovations in projector technology like these have continued to make us number 1 in the world of projectors since 2001².





SUPERIOR RELIABILITY



Inorganic LCD panels and phosphor wheel

Currently, light sources for laser projectors mainly use blue diodes containing phosphor due to the efficiency of the light and cost benefits. Our newly developed phosphor wheel is made of inorganic material with superior light and heat-resistance to deliver excellent reliability. We've also developed inorganic LCD panels, key components of imaging devices. Combining an inorganic phosphor wheel with inorganic LCD panels in a laser projector results in bright, vibrant images for extremely long periods.

A quality revolution

Take presenting into the future with 4K enhancement technology that digitally upscales Full HD 1080p content by shifting pixels diagonally by 0.5 pixels to effectively double resolution. This gives viewers the 4K experience, with improved texture, exceptional sharpness, clarity and detail.

Organic vs. inorganic

		ganic luminum, etc.)	Organic (Paper, wood, plastic, etc.)		
- Cight-resistance	YES		NO		
Heat-resistance	YES	9	NO	\$	

Unlike organic substances, inorganic substances do not contain carbon


The perfect combination


Our 3LCD technology combines high resolution, brightness and rich colours to produce vivid, engaging images even in brightly lit rooms. Our 3-chip solid-state optical engines optimise white balance and black colour matching for seamless blending. Equally high White and Colour Light Output makes images consistent and three times brighter than 1-chip DLP projectors¹, and with no rainbow effect.

Larger than life

Project every corner-to-corner detail of Full HD widescreen content with standard native WUXGA resolution. Deliver the ultimate viewing experience with the world's first 12,000lm WUXGA laser model³, the EB-L1500U/1505U.

4k enhancement





Full HD

Simulated images

Wider colour gamut

Achieve up to three times the colour gamut of 1-chip DLP projectors with Epson's HTPS panels. This core technology produces more vibrant colours with more accurate colour reproduction. You can also adjust hue, saturation and brightness for each colour in the RGB and CMY colour models.










Epson 3LCD technology – Conventional projector 3 times brighter than using 1-chip DLP technology





SUPERIORITY IN NUMBERS

Take control of brightness with precise adjustment in increments of 1% and a constant brightness mode that maintains brightness at a specified level to match any venue or subject for up to 56,000 hours. Auto colour correction is also on hand to keep colours consistent and whites bright.

Long-term performance

Experience complete peace of mind with the 20,000 hours or 5 year warranty (whichever comes first). This ensures reliable long-term performance and gives you the freedom to concentrate on your presentations.

Just about anywhere

Rotate your projector through up to 360° in any direction and bring floors and ceilings into play. Create eye-catching images in surprising settings without distortion or loss of brightness, even on a corner or curve.

Compact power

Add power to your presentations with the ground-breaking 12,000lm WUXGA EB-L1500U/EB-L1505U, which is up to 15% smaller and 10% lighter than competitor 12,000lm products⁴ for easy integration into smaller spaces.

New light, new quality standards

Enjoy the best picture quality in bright and dark scenes with high-speed control of contrast levels and the transition between the two, thanks to the new laser light source. Also, edge blending technology seamlessly joins images produced by more than one projector.

2,000:1 native contrast ratio

Project images with clear contrast even in daylight or with lights on. A high brightness up to 12,000lm and a native contrast ratio of 2,000:1 ensure super dark blacks and super bright whites. There's even an inner sensor to adjust the intensity of blue and yellow light to make whites even more appealing.

Two screens

Compare and contrast different subjects and enhance presentations with the split screen function that makes it easy to project images from two different sources simultaneously.

THE POWER TO PRESENT

These projectors give you the power to surpass your presenting goals. They make so much more possible with versatile tools and features that are built to meet the changing demands and help you to exceed the quality expectations of the most discerning audiences.



Multi-projector perfection

Create stunning large scale images using additional projectors, with seamless tiling and blending, optimised white balance and better black colour matching between units⁵. Make precise adjustments to the start position, edge width and area of the black level in the blend and save time by reducing overlapping areas.

A range of lenses

Choose the ideal motorised lens for your venue from a wide range including an ultra-short-throw (UST) zero offset lens⁶ which produces a 200-inch screen from only 1.5m away. A choice of lenses also makes it easier to use an existing ceiling or wall mount.

Versatile installation

Project perfectly uniform images with the powered lens with new stepping motor, for very precise image adjustments up to +/- 67% vertical and +/-30% horizontal. This can be done manually or by remote control, and is very useful for edge blending and stacking. Store up to 10 lens settings, while a new OSD Control Pad function gives you control via the web or a smart device.

Wide connectivity

Get set up and integrated quickly and easily with a wide range of inputs. Support for HD-SDI/HDBaseT provides Full HD video and audio via Ethernet, while the 3G-SDI input on the EB-L1500U/ EB-L1505U/EB-L1405U allows projection of fully uncompressed images.

Built-in camera

Keep images consistent and maintenance to a minimum with the built-in camera. This detects images that have become uneven over time, detect subtle inconsistencies between multiple projectors and enables automatic colour correction. You can choose whether to check manually or set up for automatic checking at regular intervals.

THE PERFECT CHOICE

Choose from a range of models that offer exceptional quality and versatility as standard but have different features to match your individual presenting needs.



EB-L1100U

- 6,000lm
- WUXGA



EB-L1405U

- 8,000lm
- WUXGA



EB-L1200U

– 7,000lm – WUXGA



EB-L1500U – 12,000lm

- WUXGA



EB-L1300U

- 8,000lm
- WUXGA



EB-L1505U

– 12,000lm – WUXGA

Accessories

Epson offers a wide range of accessories including lenses, ceiling mounts and wireless LAN adapter. To view the full range visit www.epson-europe.com



Ceiling mount low ELPMB47/ELPMB48 Tailor-made ceiling mounts for easy installation and security



Wireless LAN adapter ELPAP10


- Easy installation USB adapter
- Make fast, secure presentations across a wireless connection with EasyMP Network Projection or Epson's iProjection app




HDBaseT transmitter ELPHD01

- Wired video/audio extender
- Three inputs are featured for easy installation: HDMI, LAN, and RS-232 to output into a CAT-5/6 cable

Connectivity



Model shown EB-L1505U



Dimensions





Model shown EB-L1505U

Features

- WUXGA native resolution
- 2,000:1 native contrast ratio
- 4k enhancement technology (\checkmark)
- Built-in camera

Lens shift/memory function A/V Mute with fade in/out

293mm

- Split screen
- Easy 360° installation



DMA Art-net Ethernet (EB-L1405/1500/1505)


185mm

Optional lens specifications

Lenstype	Ultra-short- throw ⁶	Short throw	Short throw	Wide throw	Wide throw	Mid throw	Mid throw	Mid throw	Mid throw	Long throw
Reference	ELPLX01*	ELPLU03	ELPLU04	ELPLW05	ELPLW06**	ELPLM08*	ELPLM09	ELPLM10	ELPLM11	ELPLL08
Order number	V12H004X01	V12H004U03	V12H004U04	V12H004W05	V12H004W06	V12H004M08	V12H004M09	V12H004M0A	V12H004M0B	V12H004L08
Lens option	9	S	Ó	Ø	S	67	6	67	6	6
Focus / Zoom type	Motorised	Motorised	Motorised	Motorised	Motorised	Motorised	Motorised	Motorised	Motorised	Motorised
Zoom ratio (Optical)	N/A	1.2×	1.2×	1.4×	1.37×	1.6×	1.6×	1.5×	1.5×	1.39×
Throw ratio	0.35:1	0.65-0.78:1	0.87 - 1.06:1	1.04 - 1.46:1		1.45 - 2.32:1	2.15 - 3.49:1	3.31 - 5.07:1	4.84 - 7.39:1	7.2 – 10.12:1
EB-L1500U/1505U models		0.48-0.57:1	0.64 – 0.78:1	0.76 - 1.07:1	1.19–1.63:1		1.58 - 2.56:1	2.43-3.71:1	3.54 - 5.41:1	5.28 - 7.72:1
Aspect ratios	16:10	16:10	16:10	16:10	16:10	16:10	16:10	16:10	16:10	16:10
F Number		2.0-2.26	2.0-2.1	2.0-2.23	1.8-2.26	1.65-2.27	1.8-2.51	1.81 – 2.4	1.81 – 2.34	1.8-2.45
Focal length (mm)	5.8	11.1 – 13.1	14.8 - 17.7	17.6-24.3	27.3-37.0	24.0-38.2	36 - 57.4	55.4 - 83.3	80.6 - 121.1	119–165.4
Screen size range (inches)	100 - 400	80 - 300	50 - 300	50 - 300	50 - 300	50 - 300	50 - 300	50 - 300	50 - 300	50 - 300
Lens shift	V: ±17% H: ±10%	V: ±67%, H: ±30%	V: ±67%, H: ±30%	V: ±67%, H: ±30%		V: ±67%, H: ±30%				
EB-L1500U/1505U models		V: ±24% H: ±10%	V: ±60% H: ±18%	V: ±24% H: ±10%	V: ±60% H: ±18%		V: ±60% H: ±18%	V: ±60% H: ±18%	V: ±60% H: ±18%	V: ±60% H: ±18%
Weight (kg)	3.5	1.8	3.1	1.45	2.95	1.2	1.9	2.2	2.2	2.2

*ELPLX01/ ELPLMO8 lens is not available on the EB-L1500U and EB-L1505U. **ELPLW06 lens is only available for the EB-L1500U and EB-L1505U.

Modular lenses and projection distances



Only representative of the EB-L1100U/EB-L1200U/EB-L1300U/EB-L1405U.

Specifications

Connectivity

	EB-L1100U	EB-L1200U	EB-L1300U	EB-L1405U	EB-L1500U/ EB-L1505U		
Technology		Eps	on 3LCD laser technol	ogy			
Resolution / aspect ratio	WUXGA / 16:10						
4k enhancement							
Contrast ratio (dynamic / native)	>2,000,000:1 / 2,000:1	>2,000,000:1 / 2,000:1	>2,000,000:1 / 2,000:1	>2,000,000:1 / 2,000:1	>2,000,000:1 / 2,000:1		
Colour and White Light Output (lumens) (standard / economy)	6,000	12,000					
Laser life (hours) (standard / economy)	20,000 / 56,000						
Image size (inches)	50 – 300						
Throw ratio		1.58 – 2.56:1					
Lens F-number (F) Focal length (f) (mm)	1.65 – 2.27 1.8 – 2.51						
Zoom ratio	1.6×						
Keystone correction (horizontal / vertical)	±30°/±45°						
Lens shift (horizontal / vertical)	±30°/±67°						
Speakers		N/A					
Noise (standard / economy) (dB)			35/29		37/31		
Power consumption (w) (on / economy / stand-by)	454/313/0.5	908 / 597 / 0.5					
Weight (kg)		22					
Dimensions W×D×H (mm)		586 × 492 × 185					
Digital	HDMI (W/HDCP2.2) x1, DVI-D x1, HDBaseT (W/HDCP2.2) x1						
Video	Input: PC Out	: (D-sub 15), Componer put: Monitor out (D-sub	Input: 3G-SDI, PC (D-sub 15), Component (5BNC) Output: Monitor out (D-sub 15)				
Control		LAN (RJ45),		DMX Art-Net (RJ45), LAN (RJ45), RS232 (IN)			
USB	USB Type A (Optional Wi-Fi, Firmware update via USB Flash Drive), USB Type B (service only)						
Audio	Input: Stereo mini x3 Output: Stereo mini x1						
Supplied accessories	Power cable, computer cable, cable cover, HDMI cable clamp, lens cap, remote control, user manual						
Projector warranty ⁷	5 years or 20,000 hours, whichever comes first						

CoverPlus365

Better Products for a Better Future[™]

- ¹ Colour Brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour Brightness will vary depending on usage conditions. Leading Epson 3LCD business and education projectors compared to leading one-chip DLP projectors, based on NPD data for June 2013 through May 2014 and PMA Research data for Q1 through Q3 2013. For more information please visit www.epson.eu/CLO
 ² Survey conducted by Futuresource Consulting Limited for the period from 2001 to 2015.
 ³ The EB-L1505U / EB-L1500U is the first and only 12,000lm WUXGA LCD laser projector on the market as of November 2015.
 ⁴ EB-L1505U / EB-L1500U dimensions of (W586 x D467 x H185) and weight (21.5kg), compared to Panasonic PT-DZ13K (W530 x D548.5 x H200) and weight (24kg) make it the smallest and lightest 12,000lm projector on the market as of November 2015.
 ⁵ Not available on the EB-L1500U/EB-L1505U.
 ⁶ Available in Autumn 2016.
- ⁶ Available in Autumn 2016.
 ⁷ Warranty offers are not available for all countries. Please contact your local Epson representative.
- For further information please contact your local Epson office or visit www.epson-europe.com

Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04 (Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece 210-8099499 Hungary 06800 147 83 Ireland 01 436 7742 Italy 02-660321 10 (0,12 c/min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 z/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min) Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

EPSON[®]