

NEC M302WS

Order Code: 60003578

NEC Professional Short-Throw Projector



The excellent price performance ratio makes this projector especially suitable for classrooms and mid-sized meeting rooms. The filter free design with dust-protected DLP light engine, very long lamp life and low power consumption results into remarkably low cost of ownership. Various innovative new ECO functions such as the Ambient Light Sensor help to significantly reduce power consumption. A vast number of input terminals boosts connectivity and allows advanced interactive multimedia capabilities.

The interactive Multi-pen option and optional DisplayNote Presenter software turn this short-throw projector into the centerpiece of a modern learning and meeting environment.

BENEFITS

Less Shadow and Glare - not standing in the light beam gives you more space to engage with your audience when presenting.

Optional Multi-pen Interactivity - with real gesture support on any kind of surface.

Robust and dust resistant - thanks to sealed DLP light engine.

Great connectivity - due to numerous analog and digital connection terminals as well as network capability.

Low cost of ownership - up to 8000h lamp life, low power consumption.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.



NaViSet
Administrator 2

IMAGE	Projection Technology	1 x 1.65 cm (0.65") 2x LVDS DMD Chip
	Native Resolution	1280 x 800 (WXGA)
	Aspect Ratio	16:10
	Contrast Ratio ¹	10000:1
	Brightness ¹	3000 ANSI Lumen (approx. 75% in Eco Mode)
	Lamp	225 W AC (135 W AC Eco Mode)
	Lamp Life [hrs]	8000 Eco / 5500 Normal / 3500 High Bright Mode
	Lens	F= 2.4, f= 6.5 mm
	Projection Factor	0.45 : 1
	Projection Distance [m]	0.56 – 1.48
	Projection Angle [°]	40.7 - 40.9
	Screen Size (diagonal) [cm] / [inch]	152.4 / 60" - 381 / 150"
	Zoom	Digital Zoom
	Focus Adjustment	Manual
	Supported Resolutions	1920 x 1080 (HDTV 1080i/60; HDTV 1080i/50); 1680 x 1050 (WSXGA+); 1600 x 1200 (UXGA); 1600 x 900 (WXGA++); 1440 x 900 (WXGA+); 1400 x 1050 (SXGA+); 1366 x 768 (WXGA); 1360 x 768 (WXGA); 1280 x 1024 (Maximum resolution of digital input); 1280 x 1024 (SXGA); 1280 x 1024 (MAC 23"); 1280 x 960 (SXGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (HDTV 720p); 1152 x 870 (MAC 21"); 1152 x 864 (XGA); 1024 x 768 (XGA); 832 x 624 (MAC 16"); 800 x 600 (SVGA); 720 x 576 SDTV 480p/480i; 720 x 576 (DVD progressive); 720 x 480 SDTV 576p/576i; 720 x 480 (SDTV 480p); 640 x 480 (VGA/MAC 13")
Frequency	Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz	
CONNECTIVITY	RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
	HDMI™	Input: 2 x HDMI™ (Deep Color, Lip sync)
	Video	Input: 1 x RCA
	Audio	Input: 1 x 3.5 mm Stereo Mini Jack; 1 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack (variable)
	Microphone	Input: 1 x 3.5 mm Monaural Mini Jack (Dynamic mic / Condenser mic)
	Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
	LAN	1 x RJ45; Optional WLAN
	USB	1 x Type A (USB 2.0 high speed); 1 x Type B
	3D Sync	Output: 1 x Mini DIN 3pin
	Video Signals	NTSC; NTSC 4.43; PAL; PAL-M; PAL60; SECAM
	REMOTE CONTROL	Remote Control
ELECTRICAL	Power Supply	100-240 V AC; 50 - 60 Hz
	Power Consumption [W]	224 (Normal) / 202 (Eco) / 2.9 (Network Stand-by) / 0.4 (Stand-by); 286 (High Bright)
MECHANICAL	Dimensions (W x H x D) [mm]	368 x 97 x 286 (without lens and feet)
	Weight [kg]	3.6
	Fan Noise [dB (A)]	30 / 30 / 38 (ECO / Normal / High Bright)
ENVIRONMENTAL CONDITIONS	Operating Temperature [°C]	5 to 40
	Operating Humidity [%]	20 to 80
	Storage Temperature [°C]	-10 to 50
	Storage Humidity [%]	20 to 80
ERGONOMICS	Safety and Ergonomics	CE; EAC; RoHS; TÜV GS
	Speakers [W]	1 x 20 (mono)
ADDITIONAL FEATURES	Special Characteristics	Ambient Light Sensor; Auto Eco Mode; Auto Power-ON Function; Automatic and manual Keystone Correction (V= +/-30°); Carbon Savings Meter; Colour Management; Constant Brightness Mode; Content Transmission via Network; Crestron RoomView; DICOM Simulation; Full 3D DLP® LINK support; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify; NaViSet Administrator 2; Off-Timer; Optional User Logo; Optional WLAN; OSD with 29 languages; Password Security System; Quick Start; Remote control and administration via LAN and RS232; Security Bar; Simple Access Point; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction
GREEN FEATURES	Energy Efficiency	75 % AV mute function; Auto ECO Mode; ECO scheduler; Green one touch ECO and AV mute button; ImageCare® Technology; Intelligent Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling
	Ecological Materials	100% recyclable packaging; Downloadable manuals; ECO packaging
	Ecological Standards	ErP compliant; RoHS compliant; WEEE
WARRANTY	Projectors	3 years pan-European service
	Lamp	6 months, max. 1000 hrs
SHIPPING CONTENT	Shipping Contents	IR Remote Control (RD-469E); Lens Cap; Mini D-SUB Signal Cable; Power Cord (3 m); Quick Setup Guide; Security Sticker; Users Manual on CD-ROM
OPTIONAL ACCESSORIES	Optional Accessories	3D Starter Kit (NP02SK3D); Cable Cover (NP05CV); DisplayNote; DLP-Link 3D Glasses (NP02GL, VolfoniFit); Interactive Unit (NP03Wi); Lamp (NP28LP); Wall Mount Kit (NP05WK); Wireless LAN module (NP02LM2 for EU, NP02LM3 for Russia)

¹ Compliance with ISO21118-2005