

# NEC UM330X

Order Code: 60003393

NEC UM330X Professional Ultra-Short-Throw Projector

Get great performance while saving the environment. Advanced Eco features help to substantially lower your operating cost without compromising on quality and flexibility. Less shadow and glare gives the presenter more space to engage with his audience and enhances the experience with interactive white boards.

The UM330X is particularly suited for classrooms and small to medium sized meeting rooms.



## DELIVERING GENUINE BENEFITS

**Get Great Performance** - while not compromising on quality and ease of use.

**Intuitive Use** - of latest Eco and projection technology due to user-centric design.

**Less Shadow and Glare** - not standing in the light beam gives you more space to engage with your audience when presenting.

**Wall-mount included** - for quick and easy installation, compatible with height adjustable systems.

**Works with various NEC Software Tools** - Including Image Express Utility Lite (WIN,MAC,iOS), Virtual Remote Tool (WIN / iOS), PC Control Utility Pro 4 / 5, Viewer PPT Converter and DisplayNote.

**Optional Multi-pen Interactivity** - with real gesture support on any kind of surface.

**Free Download of Multi-Display Management Software** - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.



NEC Factory Preset  
**DICOM**  
SIMULATION



## OUTSTANDING PERFORMANCE

- **Ultra Short-Throw Projection** with 0.36:1 throw ratio
- **Minimized Cost of Ownership** due to long lamp life and filter cleaning intervals
- **Innovative ECO Functions** to reduce power consumption
- **Great Connectivity** due to numerous analog and digital connection terminals, network capability as well as optional wireless connection



**SPECIAL CHARACTERISTICS**

AMX Beacon, Auto Eco Mode, Carbon Savings Meter, Colour Management, Content Transmission via Network, Contrast Ratio 3000:1 with Iris, Crestron RoomView, DICOM Simulation, Direct Power-Off Function, High Altitude Mode, Kensington security slot, Keypad Lock, Magnify, Manual vertical Keystone Correction (V=±10°), NaViSet Administrator 2, Optional User Logo, Optional WLAN, OSD with 29 languages, Password Security System, PJ LINK, Quick On/Off, Remote control and administration via LAN and RS232, Security Bar, Test Pattern, USB Display, USB Viewer for JPEG, Virtual Remote for direct PC control, Wall Colour Correction



**Energy Efficiency** 75% AV mute function; Auto ECO Mode; ECO scheduler; Green one touch ECO and AV mute button; Intelligent Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling

**Ecological Materials** 100% recyclable packaging; Downloadable manuals; ECO packaging

**Ecological Standards** ErP compliant; RoHs compliant

**Technical Specification NEC UM330X**

<b>IMAGE</b>	
Projection Technology	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA
Native Resolution	1024 x 768 (XGA)
Aspect Ratio	4:3
Contrast Ratio <sup>1</sup>	3000:1
Brightness <sup>1</sup>	3300 ANSI Lumen (approx. 75% in Normal, 60% in Eco Mode)
Lamp	265 W High Bright / 195 W Normal / 160 W Eco Mode
Lamp Life [hrs]	6000 Eco / 3500 Normal / 3000 High Bright Mode
Lens	F= 1.8, f= 4.78 mm
Projection Factor	0.36 : 1
Projection Distance [m]	0.11 – 0.51
Projection Angle [°]	53.1
Screen Size (diagonal) [cm] / [inch]	Maximum: 296.2 / 116.6"; Minimum: 156.2 / 61.5"
Zoom	1.4 x Digital Zoom
Focus Adjustment	Manual
Supported Resolutions	1920 x 1200 (WUXGA); 1920 x 1080 (HDTV 1080i/60; HDTV 1080i/50); 1680 x 1050 (WSXGA+); 1600 x 1200 (UXGA); 1600 x 900 (WXGA++); 1440 x 900 (WXGA+); 1400 x 1050 (SXGA+); 1366 x 768 (WXGA); 1360 x 768 (WXGA); 1280 x 1024 (SXGA); 1280 x 1024 (MAC 23"); 1280 x 960 (SXGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (HDTV 720p); 1152 x 870 (MAC 21"); 1152 x 864 (XGA); 1024 x 768 (XGA); 832 x 624 (MAC 16"); 800 x 600 (SVGA); 720 x 576 SDTV 480p/480i; 720 x 480 SDTV 576p/576i; 640 x 480 (VGA/MAC 13")
Frequency	Horizontal: 15 – 100 kHz (RGB: 24 kHz – 100 kHz); Vertical: 50 – 120 Hz
<b>CONNECTIVITY</b>	
RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
HDMI™	Input: 2 x HDMI™ (Deep Color, Lip sync)
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 1 x 3.5 mm Microphone Jack; 2 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack (variable)
Microphone	Input: 1 x 3.5 mm Stereo Mini Jack (Dynamic mic)
Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45; Optional WLAN
USB	1 x Type B; 2 x Type A (USB 2.0 high speed)
Video Signals	NTSC; NTSC 3.58; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM
<b>REMOTE CONTROL</b>	
Remote Control	Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Direct Source Select; Freeze; Help Eco Mode; Help-function; ID set; Picture Adjust; Presentation and Mouse Control
<b>ELECTRICAL</b>	
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	263 (Normal) / 233 (Eco) / 8 (Network Stand-by) / 0.4 (Stand-by); 344 (High Bright)
<b>MECHANICAL</b>	
Dimensions (W x H x D) [mm]	378 x 112 x 428 (without lens and feet)
Weight [kg]	5.7
Fan Noise [dB (A)]	28 / 28 / 35 (ECO / Normal / High Bright)
<b>ENVIRONMENTAL CONDITIONS</b>	
Operating Temperature [°C]	5 to 40
Operating Humidity [%]	20 to 80 non-condensing
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80 non-condensing
<b>ERGONOMICS</b>	
Safety and Ergonomics	CE; Gost-R; RoHS; TÜV GS
Speakers [W]	1 x 16 (mono)
<b>WARRANTY</b>	
Projectors	3 years pan-European service
Lamp	6 months, max. 1000 hrs
<b>SHIPPING CONTENT</b>	
Shipping Contents	IR Remote Control (RD-448E); Mini D-SUB Signal Cable; Power Cord (3 m); Quick Setup Guide; Security Sticker; Users Manual on CD-ROM; Wall-mount kit NP04WK
<b>OPTIONAL ACCESSORIES</b>	
Optional Accessories	DisplayNote; Interactive Unit (NP02Wi, NP03Wi); Lamp (NP17LP-UM); Mouse Receiver (NP01MR); Wireless LAN module (NP02LM2/3)

<sup>1</sup> Compliance with ISO21118-2005