

# **NEC UM280Xi**

Order Code: 60003571

## NEC UM280Xi Professional Interactive Ultra-Short-Throw Projector

Get great performance while saving the environment. Advanced Eco features help to substantially lower your operating cost without compromising on quality and flexibility. Less shadow and glare gives the presenter more space to engage with his audience and enhances the experience when using the integrated interactive whiteboard function.

The UM280Xi is particularly suited for classrooms and small to medium sized meeting rooms.

#### **DELIVERING GENUINE BENEFITS**

**Integrated interactivity** - based on eBeam® technology including application software for business and corporate users.

**Less Shadow and Glare** - not standing in the light beam gives you more space to engage with your audience when presenting.

**Wall-mount included** - for quick and easy installation, compatible with height adjustable sytems.

Works with various NEC Software Tools - Including Image Express Utility Lite (WIN,MAC,iOS), Virtual Remote Tool (WIN / iOS), PC Control Utility Pro 4 / 5, Viewer PPT Converter and DisplayNote.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.











### **OUTSTANDING PERFORMANCE**

- . Integrated interactivity transforms any flat surface into an interactive workspace
- . Ultra Short-Throw Projection with 0.36:1 throw ratio
- . Minimized Cost of Ownership due to long lamp life and filter cleaning intervals
- Innovative ECO Functions to reduce power consumption
- Great Connectivity due to numerous analog and digital connection terminals, network capability as well as optional wireless connection



#### SPECIAL CHARACTERISTICS

AMX Beacon, Auto Eco Mode, Carbon Savings Meter, Colour Management, Content Transmission via Network, Contrast Ratio 3000:1 with Iris, Crestron RoomView, DICOM Simulation, Direct Power-Off Function, High Altitude Mode, Including interactive module and pen, Kensington security slot, Keypad Lock, Magnify, Manual vertical Keystone Correction (V= ±10°), NaViSet Administrator 2, Optional User Logo, Optional WLAN, OSD with 29 languages, Password Security System, PJ LINK, Quick On/Off, Remote control and administration via LAN and RS232, Security Bar, Test Pattern, USB Display, USB Viewer for JPEG, Virtual Remote for direct PC control, Wall Colour Correction



Energy Efficiency 75% AV mute function; Auto ECO Mode; ECO scheduler; Green one touch ECO and AV mute button; Intelligent Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling

Ecological Materials 100% recyclable packaging; Downloadable manuals; ECO packaging

Ecological Standards ErP compliant; RoHs compliant

Technical Specification NEC UM280Xi	
IMAGE	
Projection Technology	3 x 1.6 cm (0.63") p-Si LCD Panel with MLA
Native Resolution	1024 x 768 (XGA)
Aspect Ratio	4:3
Contrast Ratio 1	3000:1
Brightness 1	2800 ANSI Lumen (approx. 75% in Normal, 60% in Eco Mode)
Lamp	230 W High Bright / 170 W Normal / 140 W Eco Mode
Lamp Life [hrs]	8000 Eco / 5000 Normal / 4000 High Bright Mode
Lens	F= 1.8, f= 4.78 mm
Projection Factor	0.36 : 1
Projection Distance [m]	0.11 - 0.51
Projection Angle [°]	53.1
Screen Size (diagonal) [cm] / [inch]	Maximum: 269.2 / 106"; Minimum: 160 / 63"
Zoom	1.4 x Digital Zoom
Focus Adjustment	Manual Manual
Supported Resolutions	1920 x 1200 (WUXGA); 1920 x 1080 (HDTV 1080i/60; HDTV 1080i/50); 1680 x 1050 (WSXGA+); 1600 x 1200 (UXGA); 1600 x 900 (WXGA++); 1440 x 900 (WXGA) +); 1400 x 1050 (SXGA+); 1366 x 768 (WXGA); 1360 x 768 (WXGA); 1280 x 1024 (MAC 23"); 1280 x 960 (SXGA); 1280 x 60 (WXGA); 1280 x 702 (MDTV 720p); 1152 x 870 (MAC 21"); 1152 x 864 (XGA); 1024 x 768 (XGA); 328 x 624 (MAC 16"); 800 x 600 (SVGA); 720 x 576 SDTV 480p/480i; 720 x 480 SDTV 576p/576i; 640 x 480 (VGA/MAC 13")
Frequency	Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz
CONNECTIVITY RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
HDMI™	Input: 2 x HDMI™ (Deep Color, Lip sync)
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 1 x 3.5 mm Stereo Mini Jack; 1 x 3.5 mm Microphone Jack; 2 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack (variable)
Microphone	Input: 1 x 3.5 mm Stereo Mini Jack (Dynamic mic)
Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45; Optional WLAN
USB	1 x Type B; 2 x Type A (USB 2.0 high speed)
Video Signals	NTSC; NTSC 3.58; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM
REMOTE CONTROL Remote Control	Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Direct Source Select; Freeze; Help Eco Mode; Help-function; ID set; Picture Adjust; Presentation and Mouse Control
ELECTRICAL Power Supply	100-240 V AC: 50 - 60 Hz
Power Consumption [W]	235 (Normal) / 212 (Eco) / 8 (Network Stand-by) / 0.4 (Stand-by); 304 (High
Tower consumption (w)	Bright)
MECHANICAL	
Dimensions (W x H x D) [mm]	378 x 112 x 428 (without lens and feet)
Weight [kg]	5.6
Fan Noise [dB (A)]	28 / 28 / 35 (ECO / Normal / High Bright)
ENVIRONMENTAL CONDITIONS	
Operating Temperature [°C]	E+0.40
' ' ' ' ' '	5 to 40
Operating Humidity [%] Storage Temperature [°C]	20 to 80 non-condensing
	-10 to 50
Storage Humidity [%]	20 to 80 non-condensing
ERGONOMICS	
Safety and Ergonomics	CE; Gost-R; RoHS; TÜV GS
Speakers [W]	1 x 16 (mono)
WARRANTY	
Projectors	3 years pan-European service
Lamp	6 months, max. 1000 hrs
·	5 months, max. 1000 m5
SHIPPING CONTENT Shipping Contents	Interactive Module (NP02Wi); IR Remote Control (RD-448E); Mini D-SUB Signal Cable; Power Cord (3 m); Quick Setup Guide; Security Sticker; Users Manual on CD-ROM; Wall-mount kit NP04WK
OPTIONAL ACCESSORIES Optional Accessories	DisplayNote; Lamp (NP16LP-UM); Mouse Receiver (NP01MR); Wireless LAN module (NP02LM2/3)

<sup>&</sup>lt;sup>1</sup> Compliance with ISO21118-2005

