# Pro8500

NETWORKABLE HIGH BRIGHTNESS PROJECTOR

120HZ AND 3D-READY

## Brilliant and 3D-ready.

The ViewSonic® Pro8500 is an advanced high brightness DLP® installation projector which includes BrilliantColor™ technology to produce more vibrant colors. The Pro8500 delivers 5000 lumens, 4900:1 contrast ratio with a 1024x768 XGA native resolution, allowing it to shine in virtually any lighting situation. The Pro8500 provides maximum mounting flexibility with a wide 1.5X optical zoom adjustment and a multitude of connectivity options including Network Display, USB, and WiFi. The filter-less design and long lamp life provide for easy maintenance and low total cost of ownership.



### SHINE BRIGHT, ANYWHERE

> Bright in virtually any setting with 5,000 lumens
Ultra-bright 5,000 lumen output makes this the perfect choice
for large boardrooms, conference halls and auditoriums.

> BrilliantColor™ technology

Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 5-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

> Stay connected

Supports multiple video timing formats from SD (NTSC, PAL, SECAM) to HD 720p, 1080i/p.

> PC-Less Slide Show Presentation

Project your pictures or images directly from a USB flash drive without a PC.

> Network Display

With its advanced management software, you can project up to 4 PCs at the same time with the ability to broadcast up to 8 projectors.

> USB Display

Project your presentations through any USB connection without the hassle of running a bulky VGA cable.

> Wireless Capability

Allow the projector to be WiFi enabled with an optional USB wireless adapter (WPD-100).

> Network control through RJ-45

Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status.

> Closed captioning

Integrated closed captioning decoder for the hearing impaired.

> Give Greener presentations and save \* Use the Eco-mode to achieve lower power consumption, reduce overall noise and extend lamp life. Filter less design saves costs and maintenance.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES











# Pro8500

### NETWORKABLE HIGH BRIGHTNESS PROJECTOR - 120HZ AND 3D-READY







### **Optional Accessories**

> Replacement Lamp	RLC-059
> Universal Ceiling Mount Kit	WMK-005
> Wireless G Presentation Gateway	WPG-360
> USB Wireless Adapter (802.11b/g/n	) WPD-100
> Extended Express Exchange®	PRJ-EE-08-03

Projection		4:3 Aspect			
Dist	ance	Wide		Tele	
M	Feet	M	Inches	M	Inches
1.5	4.92	1.22	47.8	0.81	31.8
1.8	5.90	1.49	57.4	0.97	38.1
2	6.56	1.62	63.7	1.08	42.4
3	9.84	2.44	95.8	1.61	63.7
5	16.40	4.05	159.5	2.69	106.0
10	32.80	8.11	319.0	5.39	212.1









ViewSonic Corporation's QMS & EMS have been registere

DISPLAY	Туре	0.7" Digital Micromirror Device (DLP™)		
	Resolution	XGA 1024x768 (Native)		
	Lens	1.5× Manual optical zoom / Manual optical focus		
	Keystone	Vertical digital keystone correction: +/- 40 degrees		
	Size	30"-300" / 0.76m-7.6m		
	Throw Distance	0.9m-10m / 3ft-32.8ft		
	Throw Ratio	1.45 – 2.18:1		
		280 watt		
	Lamp			
	Lamp Life (Normal / Eco-mode)			
	Brightness	5000 Lumens		
	Contrast Ratio	4900:1 (dynamic)		
	Aspect Ratio	4:3 (native), 16:9, 16:10, Auto		
	Color Gamut	70% NTSC 1931 CIE		
INPUT SIGNAL	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, SECAM (B, D, G, K, K1, L), SD 480i and 576i, ED 480p a 576p, HD 720p, 1080i and 1080p		
	Frequency	Fh: 31–100KHz, Fv: 48–120Hz		
COMPATIBILITY		VGA to UXGA		
COMPATIBLETT	Mac <sup>®</sup>	Up to UXGA (scaled)		
COMMITCEOR				
CONNECTOR	RGB Input	15-pin mini D-sub (x2)		
	RGB Output	15-pin mini D-sub		
	Digital Input	HDMI 1.3		
	Component	RCA (x3)		
	Composite Input	RCA jack		
	S-video Input	4-pin mini-DIN		
	USB	Type A: for PC-less slide show presentation – supports JPEG, BMP, TIFF, PNG, GIF from USB flash drive, optional wireless USB adapter		
		Mini-B: for direct presentation from PC (not Mac compatible		
	Audio Input	3.5mm mini jack (x2), RCA (L/R) x1		
	Audio Output	3.5mm mini jack (xz), RCA (L/K) X1		
		<del></del>		
	Mic Input	3.5mm mini jack		
	Screen Trigger	3.5mm (12V/1A)		
	Control	RS-232 (DB-9)		
	Network	RJ-45		
AUDIO	Speaker	10W (x2)		
POWER	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)		
	Consumption	350W (typ) / <1W (stand-by mode)		
CONTROLS	Basic	Power, keystone/arrow keys, left/blank, menu/exit,		
		right/panel key lock, enter, source		
	OSD	<b>Picture:</b> Brightness, Contrast, Color Setting, User Color, Auto Keystone, Keystone, Aspect Ratio, Image, White		
		Intensity, Gamma, 3D Sync, 3D Sync Invert Video/Audio: Frequency, Tracking, H Position, V Position, Overscan, Noise Reduction, Video Setting, Audio Setting		
		Microphone Volume, Speaker Volume, Mute Setting: Manual Position, Projection, Signal Type, Power		
		Saving, Auto Source, Eco-mode, Filter Mode, High Altitud OSD Timeout, OSD Transparency, Presentation Timer		
		Information: Input Source, Resolution, H Frequency, V		
		Frequency, MAC Address, Filter Hours, Filter Hours Reset		
		Lamp Hours, Lamp Hours Reset, Factory Default		
		Option: Blank Screen, Password, Start up Screen, Close		
		Captions, Green Mode, DC 12V, Others, Function, Test		
		Pattern, Quick Power ON, Quick Cooling		
ODEDATING		Network: Wired LAN, Wireless LAN, Network Restart		
OPERATING	<u>Temperature</u>	32°F-104°F (0°C-40°C)		
CONDITIONS	Humidity	10%–90% (non-condensing)		
	Altitude	0~6,000 ft (1,800m), operational up to 10,000 ft (3048m)		
NOISE LEVEL	Normal / Eco-mode	32dB / 27dB		
DIMENSIONS	Physical	13.1 × 4.3 × 10.4 (in) / 333× 110 × 263 (mm)		
(W x H x D)	Packaging	16.3 × 14.8 × 7.5 (in) / 414 ×375.9 × 190.5 (mm)		
WEIGHT	Net	8.5 lb (3.86 kg)		
	Gross	11.8 lb (5.36 kg)		
REGULATIONS	51033	CB, RoHS, SVHC, WEEE, UL/cUL, FCC-B, ICES-004, TUV-S (Argentina), NOM, PSB, C-tick, KC, CE, GOST-R, Hygienic		
PACKAGE CONTENTS		UKrSEPRO, CCC ViewSonic projector, power cable, VGA cable, remote		
		control/laser with batteries, lens cap, Quick Start		
		Guide, ViewSonic Wizard DVD (with User Guide), soft		
		· · · · · · · · · · · · · · · · · · ·		
MAADDA NITY		carrying case.		
WARRANTY		3-year limited warranty on parts, 1-year limited warranty		
		ON LARDO LET VOAR EVENESS EVCHANCIO SORVICO		

#### Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

\*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications and availability subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved [15868-00B-10/11] Pro8500-1

