Pro8400

HIGH BRIGHTNESS 1080P PROJECTOR

PROFESSIONAL GRADE INSTALLATION

See it all in any venue.

The ViewSonic® Pro8400 is an advanced high brightness DLP® installation projector which includes BrilliantColor™ technology to produce more vibrant colors. The Pro8400 delivers 4000 lumens with a 1920x1080 (1080p) superb image resolution, allowing it to shine in virtually any lighting situation. The Pro8400 provides maximum mounting flexibility with a wide 1.5X optical zoom adjustment and a multitude of connectivity options including Network Display, USB, and WiFi. The filter-less design and long lamp life provide for easy maintenance and low total cost of ownership.



OPTIMIZE YOUR OPTIONS

> Bright in virtually any setting with 4,000 lumens
Ultra-bright 4,000 lumen output makes this the perfect choice for large boardrooms, conference halls and auditoriums.

> BrilliantColor™ technology

Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

> Advanced connectivity

With dual HDMI, component, composite and S-video inputs.

> Connect anywhere

Present up to 8 projectors at the same time or allow up to 4 presenters to connect to a single projector over wireless or RJ45 network.

> Stay connected

Supports multiple video timing formats from SD (NTSC, PAL & SECAM) to HD 1080p.

> Network control through RJ45

> Give Greener presentations and save

Use the Eco mode to achieve lower power consumption, reduce overall noise and extend lamp life.

> Closed captioning

Integrated closed captioning decoder for the hearing impaired.















Pro8400

HIGH BRIGHTNESS 1080P PROJECTOR - PROFESSIONAL GRADE INSTALLATION







Optional Accessories

| > Replacement Lamp | RLC-059 |
|--------------------------------------|--------------|
| > Universal Ceiling Mount Kit | WMK-005 |
| > Wireless G Presentation Gateway | WPG-360 |
| > USB Wireless Adapter (802.11 b/g/n |) WPD-100 |
| > Extended Express Exchange® F | PRJ-EE-08-03 |

| Projection Distance | | 4:3 As Wide | | | spect Tele | | |
|------------------------|-------|----------------|--------|--|---------------|--------|--|
| M | Feet | M | Inches | | M | Inches | |
| 1.5 | 4.92 | 1.22 | 47.8 | | 0.81 | 31.8 | |
| 1.8 | 5.90 | 1.49 | 57.4 | | 0.97 | 38.1 | |
| 2 | 6.56 | 1.62 | 63.7 | | 1.08 | 42.4 | |
| 3 | 9.84 | 2.44 | 95.8 | | 1.61 | 63.7 | |
| 5 | 16.40 | 4.05 | 159.5 | | 2.69 | 106.0 | |
| 10 | 32.80 | 8.11 | 319.0 | | 5.39 | 212.1 | |









ViewSonic Corporation's QMS & EMS have been registered

| DISPLAY | Type | 0.7" Digital Micromirror Device (DLP™) | | | |
|------------------|-------------------------------|--|--|--|--|
| | Resolution | 1920×1080 (1080p) | | | |
| | Lens | 1.5× Manual optical zoom / Manual optical focus | | | |
| | Keystone | Vertical digital keystone correction: +/- 20 degrees | | | |
| | Size | 30"-300" / 0.76m-7.6m | | | |
| | Throw Distance | 0.9m-10m / 3ft-32.8ft | | | |
| | Throw Ratio | 1.4 – 2.14:1 | | | |
| | Lamp | 280 watt | | | |
| | Lamp Life (Normal / Eco-mode) | 4000 / 5000* hours | | | |
| | Brightness | 4000 Lumens | | | |
| | Contrast Ratio | 2600:1 (typ), 3000:1 (dynamic) | | | |
| | Aspect Ratio | 16:9 (native) and 4:3 | | | |
| | Color Gamut | 70% NTSC 1931 CIE | | | |
| INPUT SIGNAL | Computer and Video | NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, | | | |
| | Computer and video | 60), SECAM (B, D, G, K, K1, L), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and | | | |
| | | 30fps), HD 720p, 1080i and 1080p (24fps, 25pfs and 30fps | | | |
| | Frequency | Fh: 31–91KHz, Fv: 48–85Hz | | | |
| COMPATIBILITY | PC | VGA to 1080p | | | |
| | Mac [®] | Up to 1080p | | | |
| CONNECTOR | RGB Input | 15-pin mini D-sub (x2) | | | |
| | RGB Output | 15-pin mini D-sub | | | |
| | Digital Input | HDMI 1.3 (x2) | | | |
| | Component | RCA (x3) | | | |
| | Composite Input | RCA jack | | | |
| | S-video Input | 4-pin mini-DIN | | | |
| | USB | Mini-B for direct presentation from computer | | | |
| | | Type A supports JPEG, BMP, TIFF, PNG, GIF from USB flash dri | | | |
| | Audio Input | 3.5mm mini jack | | | |
| | Audio Output | 3.5mm mini jack | | | |
| | Control | RS-232 (DB-9) | | | |
| | Network | RJ-45 | | | |
| | Screen Trigger | 0.35 plug (12V/1A) | | | |
| AUDIO | Speaker | 10W (x2) | | | |
| POWER | Voltage | 100~240VAC (Auto Switching), 50/60Hz (universal) | | | |
| POWER | Consumption | | | | |
| CONTROLS | <u> </u> | 360W (max) / <1W (stand-by mode) | | | |
| CONTROLS | Basic | Power, keystone/arrow keys, left/blank, menu/exit, | | | |
| | 020 | right/panel key lock, auto, mode/enter, source | | | |
| | OSD | Picture: Brightness, Contrast, Color Setting, Keystone, | | | |
| | | Aspect Ratio, Image, White Intensity, Gamma | | | |
| | | Computer Image: Frequency, Tracking, H Position, V Position | | | |
| | | Video Image: Saturation, Sharpnes, Tint | | | |
| | | Setting: Menu Position, Projection, Signal Type, Lamp | | | |
| | | Hour, Lamp Hour Reset, Filter Mode, Filter Hours, Filter Hours Reset, Power Saving, Auto Source, Eco-mode, Hig | | | |
| | | Altitude, OSD Timeout Advance: Blank Screen, Password Word, Screen Capture, | | | |
| | | Start up Screen, Digital Zoom, DCR, Close Captions | | | |
| OPERATING | Tomporatura | 32°F–104°F (0°C–40°C) | | | |
| | Temperature Humidity | 10%–90% (non-condensing) | | | |
| CONDITIONS | | | | | |
| MOICE LEVEL | Altitude | 0~6,000 ft (1,800m), operational up to 10,000 ft (3048m) | | | |
| NOISE LEVEL | Normal / Eco-mode | 33dB / 29dB 13.1 × 4.8 × 10.4 (in) / 232.7 × 131.0 × 244.2 (mann) | | | |
| DIMENSIONS | Physical | 13.1 × 4.8 × 10.4 (in) / 332.7 × 121.9 × 264.2 (mm) | | | |
| (W x H x D) | Packaging | 16.3 × 7.5 × 14.8 (in) / 414 ×190.5 × 375.9 (mm) | | | |
| WEIGHT | Net | 8.5 lb (3.86 kg) | | | |
| | Gross | 11.8 lb (5.36 kg) | | | |
| REGULATIONS | | CB, RoHS, SVHC, WEEE, UL/cUL, FCC-B, ICES-004, TUV- (Argentina), NOM, PSB, C-tick, KC, CE, GOST-R, Hygienic UKrSEPRO, CCC | | | |
| PACKAGE CONTENTS | | ViewSonic projector, power cable, VGA cable, HDMI cable remote control/laser with batteries, lens cap, Quick Start Guide, ViewSonic Wizard DVD (with User Guide), soft | | | |
| WARRANTY | | carrying case. 3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service. | | | |

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications and availability subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved [15866-00B-10/11] Pro8400-1

